MATERIAL SAFETY DATA SHEET



1. Product and Company Identification

Material name AKWASEAL™ HC

Version # 05

Revision date 24-February-2011

Chemical description Liquid
CAS # Mixture
Manufacturer information CETCO

Building Materials Group 2870 Forbs Avenue

Hoffman Estates, IL 60192 US safety.data@amcol.com http://www.cetco.com/

General Information (800) 527-9948 CHEMTREC® (800) 424-9300

2. Hazards Identification

Emergency overview Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin

contact. Prolonged or repeated exposure increases the risk.

Potential health effects

Routes of exposure Inhalation. Skin contact.

Eyes Irritating to eyes. Symptoms include itching, burning, redness and tearing.

Skin Substance causes moderate skin irritation. May cause sensitization by skin contact.

Inhalation May cause irritation of respiratory tract. May cause sensitization by inhalation.

Ingestion Irritating to mouth, throat, and stomach. Ingestion of this product may cause nausea, vomiting and

diarrhea.

Signs and symptoms Cough. Discomfort in the chest. Shortness of breath.

3. Composition / Information on Ingredients

Components	CAS#	Percent	
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	9016-87-9	40 - 60	

Composition comments This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if

irritation develops or persists.

Skin contact Wash off immediately with plenty of water. Remove and isolate contaminated clothing and shoes.

Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention immediately.

Ingestion If material is ingested, immediately contact a physician or poison control center. Do not induce

vomiting without medical advice. If swallowed, rinse mouth with water (only if the person is

conscious).

Notes to physician Symptoms may be delayed. Keep under medical supervision for at least 48 hours. Provide

general supportive measures and treat symptomatically.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire Fighting Measures

Flammable properties Containers may explode when heated.

Extinguishing media

Suitable extinguishing Carbon dioxide (CO2). Alcohol foam. Water spray. Dry chemical. Foam.

media

Material name: AKWASEAL™ HC

Protection of firefighters

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in

flame. Cool containers with flooding quantities of water until well after fire is out.

Fire fighting

equipment/instructions

Move containers from fire area if you can do it without risk. Do not scatter spilled material with high pressure water streams. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in

flame. Cool containers with flooding quantities of water until well after fire is out.

Specific methods In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

6. Accidental Release Measures

Personal precautions Ensure adequate ventilation. Use personal protective equipment. Do not touch or walk through

spilled material. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Methods for containment Methods for cleaning up Prevent further leakage or spillage if safe to do so.

Stop leak if you can do so without risk. Dike the spilled material, where this is possible.

Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area

thoroughly with water. Ventilate the contaminated area.

7. Handling and Storage

Handling Wash hands after handling and before eating. When using do not eat or drink. Avoid contact with

skin and eyes. Do not get this material in your eyes, on your skin, or on your clothing. Do not

handle or store near an open flame, heat or other sources of ignition.

Storage Keep locked-up. Keep out of the reach of children. Keep this material away from food, drink and

animal feed. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Keep away from heat,

sparks, and flame.

8. Exposure Controls / Personal Protection

Engineering controlsUse process enclosures, local exhaust ventilation, or other engineering controls to control

airborne levels below recommended exposure limits. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection

must be worn.

Personal protective equipment

Eye / face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and

chemical safety goggles plus a face shield. Use of butyl rubber or nitrile gloves is recommended

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the

positive pressure mode with emergency escape provisions.

General hygiene considerations

Keep away from food and drink. When using do not smoke. Use good industrial hygiene practices

in handling this material. Eye wash fountain and emergency showers are recommended.

9. Physical & Chemical Properties

Appearance Not available.

Color Brown.

Odor Slightly. Musty.
Odor threshold Not available.
Physical state Not available.

Form Liquid.

pH Not available.
 Melting point/Freezing point Not available.
 Boiling point Not available.
 Flash point Not available.
 Evaporation rate Not available.
 Flammability limits in air, upper, Not available.

% by volume

Material name: AKWASEAL™ HC

Flammability limits in air, lower, Not available.

% by volume

Vapor pressureNot available.Vapor densityNot available.Specific gravityNot available.

Relative density 0.8881 g/cm3 estimated

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

VOC

Not available.

Not available.

Not available.

120 - 150 cps

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions. No hazards to be especially mentioned.

Conditions to avoid Direct sources of heat. Keep away from water.

Incompatible materials This product may react with strong oxidizing agents. Reaction with water may generate much heat

which will increase the concentration of fumes in the air.

Hazardous decomposition

products

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. and hydrogen cyanide (hydrocyanic acid)

Possibility of hazardous

reactions

Hazardous polymerization can occur with elevated temperatures. Hazardous polymerization can occur with contact with alkalies. Hazardous polymerization can occur with metallic catalysts.

11. Toxicological Information

Toxicological data

Product	Test Results
AKWASEAL™ HC (Mixture)	Acute Dermal LD50 Rabbit: 15644 mg/kg estimated
	Acute Dermal LD50 Rat: 15644 mg/kg
	Acute Inhalation LC50 Rat: 4 mg/l/4h
	Acute Oral LD50 Rabbit: 76.67 ml/kg estimated
	Acute Oral LD50 Rat: 53316 mg/kg
Components	Test Results
POLYMETHYLENE POLYPHENYLENE ISOCYANATE (9016-87-9)	Acute Dermal LD50 Rabbit: 9400 mg/kg
	Acute Inhalation LC50 Rat: 490 mg/l/4h
	Acute Oral LD50 Rat: 49000 mg/kg

Sensitization May cause sensitization by inhalation and skin contact.

Local effects Harmful by inhalation. Irritating to respiratory system and skin.

Chronic effects Repeated or prolonged contact causes sensitization, asthma and eczemas. Repeated or

prolonged skin contact may cause allergic reactions with susceptible persons.

Carcinogenicity Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

POLYMETHYLENE POLYPHENYLENE ISOCYANATE 3 Not classifiable as to carcinogenicity to humans.

(CAS 9016-87-9)

MutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Further information Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory

conditions, should not work with isocyanates.

12. Ecological Information

Ecotoxicological data

Product Test Results

AKWASEAL™ HC (Mixture) EC50 Daphnia: >= 1000 mg/l 24.00 Hours

Material name: AKWASEAL™ HC MSDS US

Product Test Results

AKWASEAL™ HC (Mixture) LC50 Fish: >= 1000 mg/l

Ecotoxicity Components of this product have been identified as having potential environmental concerns.

Environmental effects We have no quantitative data concerning the ecological effects of this product.

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructions Dispose in accordance with all applicable regulations.

14. Transport Information

DOT

Basic shipping requirements:

UN number UN3148

Proper shipping name Water-reactive liquid, n.o.s., solution (POLYMETHYLENE POLYPHENYLENE ISOCYANATE)

Hazard class 4.3
Packing group III

Additional information:

Special provisions IB2
Basic shipping requirements:
Labels required 4.3

Additional information:

Packaging exceptionsNonePackaging non bulk203Packaging bulk242ERG number138

DOT

Packages less than 83 lbs

Basic shipping requirements:

UN number UN3148

Proper shipping name Water-reactive liquid, n.o.s., solution (POLYMETHYLENE POLYPHENYLENE ISOCYANATE)

Hazard class 4.3 Packing group III

Additional information:

Special provisions IB2
Basic shipping requirements:
Labels required 4.3

Additional information:

Packaging exceptions
Packaging non bulk
Packaging bulk
ERG number

None
203
242
138





Packages less than 83 lbs

Material name: AKWASEAL™ HC

15. Regulatory Information

US federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

POLYMETHYLENE POLYPHENYLENE ISOCYANATE 1.0 %

(CAS 9016-87-9)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

POLYMETHYLENE POLYPHENYLENE ISOCYANATE

(CAS 9016-87-9)

CERCLA (Superfund) reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes

Inventory name

Section 302 extremely

hazardous substance

No

No

Section 311 hazardous

Country(s) or region

chemical

Inventory status

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

US - New Jersey Community RTK (EHS Survey): Reportable threshold POLYMETHYLENE POLYPHENYLENE ISOCYANATE

(CAS 9016-87-9)

16. Other Information

State regulations

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

This product does not contain a chemical known to the State of California to cause cancer, birth

under applicable regulations.

defects or other reproductive harm.

This safety datasheet only contains information relating to safety and does not replace any **Further information**

product information or product specification.

Material name: AKWASEAL™ HC MSDS US

4488 Version #: 05 Revision date: 24-February-2011 Print date: 24-February-2011

On inventory (yes/no)*

HMIS ratings



NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

24-February-2011