

SAFETY DATA SHEET

1. Identification

Product identifier ENVIROSHEET® LT

Other means of identificationNot available.Recommended useNot available.Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CETCO

Address 2870 Forbs Avenue

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/
E-mail safety.data@amcol.com

Emergency phone number

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1B

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT	PETROLEUM ASPHALT	8052-42-4	60 - < 80
CALCIUM CARBONATE	LIMESTONE	1317-65-3	10 - < 30
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [BASEOIL UNSPECIFIED] (CONC>=0.1%)		64742-52-5	10 - < 20
Other components below reportable	e levels		10 - < 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Material name: ENVIROSHEET® LT

Inhalation If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if

cough or other symptoms develop.

4826 Version #: 05 Revision date: 02-May-2014 Print date: 02-May-2014

Wash off with warm water and soap. Get medical attention if irritation develops or persists. Skin contact

Immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention if Eye contact

irritation develops or persists.

If swallowed, rinse mouth with water (only if the person is conscious). Ingestion may cause Ingestion

Direct contact with eyes may cause temporary irritation.

transient irritation of throat, stomach and gastrointestinal tract. Consult a physician if necessary.

Give several glasses of water.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry powder. Dry chemical, CO2, water spray or regular foam. Carbon dioxide (CO2).

Unsuitable extinguishing media

Specific hazards arising from

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Special protective equipment

Firefighters should wear full protective clothing including self contained breathing apparatus.

and precautions for firefighters Fire-fighting

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

During fire, gases hazardous to health may be formed.

equipment/instructions Specific methods

(approved or equivalent) and full protective gear. Move containers from fire area if you can do so without risk.

General fire hazards

the chemical

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water. Stop the flow of material, if this is without risk. Sweep up or gather material and place in appropriate container for disposal. For waste disposal, see section 13 of the SDS. Containment of this material should not be necessary.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. No special environmental precautions required.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged or repeated skin contact with this material. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks, and flame. Store in a cool, dry place out of direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CALCIUM CARBONATE (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Additional components	Туре	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	PEL	5 mg/m3	Respirable fraction.
•		15 mg/m3	Total dust.

Material name: ENVIROSHEET® LT

SDS US 4826 Version #: 05 Revision date: 02-May-2014 Print date: 02-May-2014

US	OSHA	Table	7-3	(29	CFR	1910	1000)
UJ.	COLIA	Iabie	2-3	123	OI 13	1310	. 10007

Additional components	Туре	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 millions of particle	Total dust.
		15 millions of particle	Respirable fraction.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
Additional components	Туре	Value	Form
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	3 mg/m3	Respirable particles
(6.16 6.14.6)		10 mg/m3	Inhalable particles.
US. NIOSH: Pocket Guide to Chemi	cal Hazards		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
CALCIUM CARBONATE (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing. When material is heated, wear gloves to protect

against thermal burns.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection

must be provided.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Use good industrial hygiene practices in handling this

material.

9. Physical and chemical properties

Appearance Fabric/Mat
Physical state Solid.
Form Solid. Roll.
Color Black.

Odor Petroleum
Odor threshold Not available.
pH Not available.

Melting point/freezing point 190 - 230 °F (87.78 - 110 °C) Initial boiling point and boiling 700 °F (371.11 °C) estimated

range

Flash point 450.0 °F (232.2 °C) Cleveland Open Cup

283.7 °F (139.8 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Material name: ENVIROSHEET® LT

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 905 °F (485 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.00 g/cm3 estimated 1.00 g/cm3 estimated

Flammability class Combustible IIIB estimated

Percent volatile Negligible 0 % estimated

Pour point >= 300 °F (>= 148.89 °C)

>= 300 °F (>= 148.89 °C)

Specific gravity 1 estimated

1 - 1.2 1 estimated

VOC (Weight %) Negligible

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Strong acids. Acids. Strong oxidizing agents. Fluorine.

Hazardous decomposition

products

Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide,

water and other products of combustion.

11. Toxicological information

Information on likely routes of exposure

IngestionExpected to be a low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact Not available.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Product Species Test Results

ENVIROSHEET® LT (CAS Mixture)

Acute Dermal

LD50 Rabbit 2722 mg/kg

Material name: ENVIROSHEET® LT 4826 Version #: 05 Revision date: 02-May-2014 Print date: 02-May-2014 Product Species Test Results

Inhalation

LC50 Rat 13.35 mg/l/4h
Components Species Test Results

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [BASEOIL UNSPECIFIED] (CONC>=0.1%) (CAS 64742-52-5)

+2-52-5)

AcuteDermal

LD50 Rabbit 2000.0001 mg/kg

Inhalation

LC50 Rat 2.18 mg/l/4h

Oral

LD50 Rat 5000.0001 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure. This material contains petroleum

asphalt. IARC has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to animals. There is only limited evidence that undiluted, steam-refined and cracking-residue asphalt are carcinogenic to animals. Additionally, IARC has concluded that

there is inadequate evidence that asphalts alone are carcinogenic to humans.

Prolonged and repeated skin contact with some solvent extracts of asphalts have produced skin cancer in animals. IARC has concluded that there is sufficient evidence for the carcinogenicity of asphalt extracts in animals. Therefore, "cutbacks" (asphalts that are diluted, dissolved, or liquefied in hydrocarbon solvents) may also be implicated as potentially carcinogenic. While brief or intermittent skin contact with this type of product is not expected to cause harm, those workers who do not practice good personal hygiene and who are exposed repeatedly via skin contact may be at risk.

Condensed asphalt fumes, which are generated under laboratory conditions and are chemically different from those found during typical asphalt operations, have been reported to cause bacterial mutations. However, inhalation of asphalt fumes by laboratory animals, during controlled studies, did not produce lung cancer. Additionally, human studies have not established a link between lung cancer and asphalt fume exposure to date.

This product may contain trace amounts of polynuclear aromatic hydrocarbons (PAHs) as naturally occurring constituents of crude oils from which asphalt is derived. Some PAHs have been shown to be carcinogenic after prolonged or repeated skin contact in laboratory animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information Information given is based on data on the components and the toxicology of similar products. No

data is available on the product itself.

12. Ecological information

Ecotoxicity No data available for this product.

Material name: ENVIROSHEET® LT

^{*} Estimates for product may be based on additional component data not shown.

Components Species Test Results

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC [BASEOIL UNSPECIFIED] (CONC>=0.1%) (CAS

64742-52-5)

 Crustacea
 EC50
 Daphnia
 1000.0001 mg/L, 48 Hours

 Fish
 LC50
 Fish
 5000.0001 mg/L, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

Not available.

15. Regulatory information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Yes

SARA 311/312 Hazardous

Yes

chomical

chemical

SARA 313 (TRI reporting)

Not regulated.

Material name: ENVIROSHEET® LT 4826 Version #: 05 Revision date: 02-May-2014 Print date: 02-May-2014

^{*} Estimates for product may be based on additional component data not shown.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

CALCIUM CARBONATE (CAS 1317-65-3)

US. Massachusetts RTK - Substance List

ASPHALT (CAS 8052-42-4)

CALCIUM CARBONATE (CAS 1317-65-3)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date01-May-2014Revision date02-May-2014

Version # 05

United States & Puerto Rico

Further information This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

NFPA ratings

1

2 0

Material name: ENVIROSHEET® LT

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.